

the Heater Treater® COMMERCIAL

the Heater Treater® - Commercial

- For Multiple Heater Applications
- Units from 50 to 150 GPM
- 304L Stainless Steel Housings
- Buna N (FDA Grade) Gaskets
- Poly-Coat Finish
- Flows in Either Direction
- Drain Adapters Included
- Minimal Maintenance Required
- 3 Year Warranty
- Assembled in the USA

Water treatment is vital for maintaining and extending the life of water heating devices. “the Heater Treater®” is the simple, low cost solution for protecting all water heating devices from the effects of hard water scaling.



HOW IT WORKS

“the Heater Treater®” is installed on the feed water line just prior to the water heating device. As the water passes through the filter cartridges, the treatment media uniquely located in the interior of the filter, slowly dissolves into the water supply providing scale protection to the heater in several ways.

FIRST: The treatment media interferes with the ability of the calcium and magnesium to crystallize or become scale when heated. This by itself is a very effective scale prevention process.

SECOND: It lays down a thin protective coating on the interior of the heater (most importantly the heat exchanger) that does not allow any scale that might be created from adhering to the interior of the heater.

LASTLY: The 5 micron filter provides added protection from rust, sediment, or debris that could affect the operation of the heater.

the Heater Treater® COMMERCIAL

SPECIFICATIONS

SYSTEM	OPERATING
Inlet/Outlet: 2" MNPT	Maximum Pressure: 75 psi
Drain Ports: ½" FNPT	Maximum Temperature: 80° F
Vent Ports: ¼" FNPT	Maximum Flow Rate: Depends on System

COMPLETE SYSTEM*	REPLACEMENT CARTRIDGES	MAX. FLOW CAPACITY	A	B	C	D	E
FAL-THT-SS-HFC-50	FAL-THT-SS-HFC50RFK	50 GPM	20 7/8"	7"	3"	10 1/4"	12"
FAL-THT-SS-HFC-100	FAL-THT-SS-HFC100RFK	100 GPM	30 7/8"	7"	3"	10 1/4"	12"
FAL-THT-SS-HFC-150	FAL-THT-SS-HFC150RFK	150 GPM	40 7/8"	7"	3"	10 1/4"	12"

*Cartridges Included

Custom Options Available Upon Request

